BUREAU OF AUTOMOTIVE REPAIR

SPECIFIC LANGUAGE OF PROPOSED REGULATIONS

THE OFFICIAL AUTOMOTIVE REPAIR DEALER'S SIGN

Legend: Deleted text is indicated by strikethrough.

Added text is indicated by underlining.

1. Amend Section 3351.3 of Article 6 of Chapter 1 of Division 33 of Title 16 of the California

Code of Regulations, to read as follows:

§ 3351.3. Display.

(a) Except as provided in subsection (b), Aall automotive repair dealers shall display the

following in a place and manner conspicuous to their customers:

(a1) A current and valid certificate of registration as an automotive repair dealer issued by

the bureau; and

(b2) An official automotive repair dealer's sign, which meets the specifications of the

Automotive Repair Act and these regulations Section 3351.4 of this article. In the event there

are multiple facilities, an official automotive repair dealer's sign shall be displayed in a place and

in a manner conspicuous to all customers at each location.

(b) When conducting business from other than the principal business address shown in an

automotive repair dealer's registration, the dealer shall provide to every customer, with the

customer's copy of the work order as provided in paragraph (3) of subdivision (a) of Section

9884.7 of the Business and Professions Code, a copy of an official automotive repair dealer's

sign that meets the following specifications:

(1) A copy of the sign shall be reproduced on a white sheet of paper, or similar material, no

less than eight and one half inches by eleven inches $(8\frac{1}{2}$ " x 11") in size.

(2) The sign shall be proportionately reduced in size to fill the page in portrait format with no

- 1 -

more than one inch (1") margins outside the right, left and bottom inset border lines.

- (3) The current business name, address of record, business telephone number and registration number of the automotive repair dealer, as shown by the bureau's records, shall be printed above the top inset border line of the sign in print no smaller than the smallest print of the reduced sign.
 - (4) No other information, printing, decoration, border or design shall be placed on the page.
 - (c) For the purpose of subsection (b), the term "provide" shall mean to give for retention.

Note: Authority cited: Section 9882, Business and Professions Code. Reference: Sections <u>9880.3</u>, 9884.6 and 9884.17, Business and Professions Code.

2. Amend Section 3351.4 of Article 6 of Chapter 1 of Division 33 of Title 16 of the California Code of Regulations, to read as follows:

§ 3351.4. Specifications for Automotive Repair Dealer's Sign.

- (a) Official automotive repair dealer signs shall meet the following specifications:
- (a1) Content.—Until June 30, 2006, Ssigns shall be worded exactly as shown in either Figure 1 or Figure 3. On and after June 30, 2006, signs shall be worded exactly as shown in Figure 3, except that an automotive repair dealer possessing a valid registration on June 30, 2006, may comply with Section 3351.3 and this section by displaying a supplementary sign, containing the bureau's Web site address. The supplementary sign shall be worded exactly as shown in Figure 5, and shall be displayed immediately below any sign that was displayed by the automotive repair dealer in compliance with Section 3351.3 and this section on and before January 1, 2006.
- (b2) Dimensions. Signs as shown in Figure 1 shall have the dimensions shown in Figure 2, signs as shown in Figure 3 shall have the dimensions shown in Figure 4, and signs as shown in Figure 5 shall have the dimensions shown in that figure.
- (e3) Sign Material. 24-gauge steel or aluminum or synthetic material of equivalent rigidity may be used. Synthetic material may be acceptable provided it meets all of the requirements herein, including durability.

- $(\underline{d4})$ Color. The background shall be semi-gloss white. All print, border stripe and divider stripes, including the State Seal shall be gloss black in color.
- (e<u>5</u>) <u>Paint.</u> Paint shall be a premium grade exterior acrylic enamel or equivalent. The silk screen/bake-on process or an acceptable equivalent may be used.
- $(\underline{\mathbf{f6}})$ Surface Preparation. All bare metal shall be etched and coated with white primer or equivalent to insure proper paint adhesion and corrosion protection.
- (g7) Print.—Largest lettering shall be 72 pt. Futura Demi "condensed;" medium lettering shall be 48 pt. Futura Bold; and smallest lettering shall be 36 pt. Futura Bold for the signs shown in Figures 1 and 3. The lettering of the supplementary sign shown in Figure 5 shall be 48 pt. Futura Bold for the message and 72 pt. Futura Demi "condensed" for the Web site address.
- (h8) General. A three and one-half inch diameter State Seal is required for the signs shown in Figures 1 and 3;
- (9) Tthe use of embossed letters or a clear protective finish coat is permitted, but not required; and.
 - (10) Tthere shall be a one-quarter inch mounting hole in each corner.
- (<u>ib</u>) Replacement. The bureau may require replacement of any sign <u>which that</u> fails to meet the outlined specifications or <u>which that</u> is no longer <u>readily</u> legible.

Note: Authority cited: Section 9882, Business and Professions Code. Reference: Sections <u>9880.3 and 9884.17</u>, Business and Professions Code.

```
[Insert Figure 3. here.]
[Insert Figure 4. here.]
[Insert Figure 5. here.]
```